




ADHESIVES

COMMERCIAL | RESIDENTIAL

COMPARISON CHART

FEATURES	<i>BrickBond</i>	<i>MasonGrip</i>	<i>OMElite</i>
Packaging	 3.5 Gal Pail	 20 oz. Sausage	 Dry Mix
Where to Use	Interior only	Interior & exterior	Interior & exterior
Best For	Fast interior thin brick & tile installs	Exterior or diverse substrates (wood, foam, metal, glass)	Panel+ system basecoat, masonry/stone installs
Moisture Resistance	Not for wet/high-moisture areas	Permanently waterproof, weather & UV proof	Passes water resistance test; not for immersion
Grab / Strength	Excellent “green grab,” ~575 psi tensile	Instant grab, ~575 psi tensile, ±25% movement	Cementitious bond, >15 psi tensile, 3000 psi compressive
Durability	Freeze/thaw stable (3 cycles)	Crack-proof, mold-resistant, vibration & impact resistant	Freeze/thaw stable, fiber reinforced, low shrinkage
Ease of Use	Ready-to-use pail; no mixing	Ready-to-use sausage; needs gun	Dry mix; add water, mix onsite
Working Time	45 min open time; cures 24 hrs	Fast grab; functional cure ~24 hrs	Pot life ~6 hrs; adjustability ~15 min
Coverage	~65–75 sq ft	~50–62 lin ft per 1/4"	~70 sq ft at 1/2" notch
VOC / Safety	<25 g/L VOC, low odor	0 VOC, odorless, no solvents	0 VOC, but contains cement & silica (PPE required)
Warranty / System Fit	1 Year	15-year warranty in Panel+ system	15-year warranty in Panel+ system